

Chartpak, Inc.
One River Road
Leeds, MA 01053
Phone: 413-584-5446 or 800-628-1910

Emergency Medical Number: 888-786-0972

Creation Date: April 5,2007

Section One: Product Information

Product Name: Grumbacher Damar Varnish
 Product Sizes: 2.5 oz., 8 oz., 16 oz., 32 oz.
 Product Class: Medium

Section Two: Ingredients

Ingredients	CAS Number	% by Weight	PEL/TLV
Turpentine	8006-64-2	70%	100 ppm
Isopropyl Alcohol	67-63-0	7%	400 ppm

Section Three: Hazards Identification

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. MAY BE HARMFUL IF SWALLOWED. EXPOSURE MAY CAUSE ALLERGIC REACTIONS.
 CONTAINS: DELTA-3-CARENE, OIL OF TURPENTINE
 KEEP OUT OF REACH OF CHILDREN.

Section Four: First Aid Measures

Inhalation: Move to fresh air.
 Skin Contact: Wash with soap and water.
 Eye Contact: Rinse immediately with water. If irritation persists, consult a physician.
 Ingestion: If swallowed, do not induce vomiting. Call a physician or poison control center immediately. Get prompt medical attention. For further health information, contact a poison control center.

This Material Safety Data Sheet is applicable to the consumer use of the following colors: 5692, 5698, 56916, 56932

Section Five: Fire Fighting Measures

Flash Point: 60F

Flammability Limits (% by volume): Lower: Not explosive Upper: Not explosive

Extinguishing Media: Foam, carbon dioxide, dry chemical,

Special Fire Fighting Measures: No special fire fighting procedures required

Unusual Fire and Explosion Hazards: Flammable liquid OSHA Class IC

Section Six: Accidental Release Measures

Remove ignition sources. Use absorbent material to clean. Keep out of water entries.

Section Seven: Handling and Storage

Handling: Use only with adequate ventilation.

Storage: Do not store or use near heat or flame. Keep container tightly capped when not in use. KEEP OUT OF REACH OF CHILDREN.

Section Eight: Exposure Controls and Personal Protection

Respiratory Protection and Special Ventilation Requirements: Use exhaust fan to remove vapors and assure adequate cross-ventilation.

Other Protective Equipment (Gloves, Goggles, Etc.): None

Work/Hygiene Practices: PRECAUTIONS: Avoid prolonged contact with skin, and ingestion. Wash hands immediately after use. Do not store or use near heat or flame. Keep container tightly capped when not in use. Use only with adequate ventilation.

Section Nine: Physical and Chemical Properties

Boiling Point: 302F Melting Point: -58F (Turpentine)

Vapor Pressure: 4 mm Hg (Turpentine) Specific Gravity: 0.86 - 0.95

Specific Vapor Density (AIR = 1): 4.84 Evaporation Rate (Butyl Acetate = 1): Not determined

Solubility in Water: Insoluble Reactivity in Water: Non-reactive

Appearance and Odor: Pale liquid; turpentine odor

Section Ten: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Excessive heat

Chemical Incompatibility: Acidic materials

Hazardous Decomposition: None known

Hazardous Polymerization: Will not occur

Section Eleven: Toxicological Information

IARC Monographs: No

National Toxicology Program: No

OSHA Regulated: No

Effects/Symptoms of Acute Exposure: May be harmful or fatal if swallowed. Overexposure may result in nausea, headache, confusion, or instability. Aspiration into the lung can cause chemical pneumonia, which can be fatal.

Effects/Symptoms of Chronic Exposure: Skin irritation and allergic reactions.

Medical Conditions Usually Aggravated By Overexposure of This Product: Unknown

Section Twelve: Ecological Information

Not available

Section Thirteen: Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations

Section Fourteen: Transport Information

ORM-D Consumer Commodity
 Flammable Liquid, n.o.s. (turpentine), 3, UN1993, III (91F TCC) Ltd Qty, EmS# F-E, S-E
 Consumer Commodity, 9, ID8000, packing instruction 910

Section Fifteen: Regulatory Information

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

Section Sixteen: Other Information

HMIS Code	
Health	2
Flammability	3
Reactivity	0
Personal Protection	C

Chartpak, Inc. is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D-4236.

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.